

NOTCH Manufacturing, Inc.



HYDRAULIC DUMP WAGONS



9 TON HYDRAULIC DUMP WAGON

DW956 HAS A 56" WIDE BOX PAN AND 74" WIDE BOX TOP, BOX IS AVAILABLE 10' OR 12' LONG, AND STRADDLES A 30" ROW

DW972 HAS A 72" WIDE BOX PAN AND 89½" WIDE BOX TOP, BOX IS AVAILABLE 10' OR 12' LONG, AND STRADDLES A 22" ROW

BOTH MODELS ARE 9 TON CAPACITY WAGONS

47° ANGLED DUMP

2½" ROCKER ARM PIVOTS WITH GREASABLE BUSHINGS CROSS MEMBERS 63/8" WIDE, 13½" CENTER TO CENTER FLOOR AND SIDES CONSTRUCTED OF 3/16" ALLOY STEEL, SIDES ARE 16" HIGH

16" X 6" OR 15" X 8" WHEELS STANDARD, OTHER SIZES AVAILABLE

2" SPINDLES, 6 BOLT HUBS WITH GREASE FITTINGS SCISSORS HOIST WITH AN ADVANTAGE LINK INCREASES THE LIFTING CAPACITY OVER A STANDARD HOIST OR CYLINDER DIRECT FROM 20-50% DURING THAT DIFFICULT FIRST FEW INCHES OF RISE

ADJUSTABLE HITCH TONGUE

MECHANICALLY OPERATING TAIL GATE INCLUDED



OPTIONAL SELF CONTAINED HYDRAULICS

ALLOWS OPERATION WITHOUT A TRACTOR OR BYPASS TRACTOR

12 TON HYDRAULIC DUMP WAGON

DW1272-16 HAS A 72" WIDE BOX PAN AND A $90\frac{1}{2}$ " BOX TOP, BOX IS 16' LONG

12 TON CAPACITY WAGON WITH A 45° ANGLED DUMP 2¾" ROCKER ARM PIVOTS WITH GREASABLE BUSHINGS

CROSS MEMBERS 63/8" WIDE, 13½" CENTER TO CENTER

FLOOR AND SIDES CONSTRUCTED OF 3/16" AND 1/4" ALLOY STEEL, SIDES ARE 20" HIGH

22.5" X 11.25" OR 22.5" X 13.5" WHEELS STANDARD, OTHER SIZES AVAILABLE

2¾" SPINDLES, 8 BOLT HUBS WITH GREASE FITTINGS
SCISSORS HOIST WITH AN ADVANTAGE LINK
INCREASES THE LIFTING CAPACITY OVER A STANDARD
HOIST OR CYLINDER DIRECT FROM 20-50% DURING
THAT DIFFICULT FIRST FEW INCHES OF RISE
ADJUSTABLE HITCH TONGUE

MECHANICALLY OPERATING TAIL GATE INCLUDED



OPTIONAL SIDE EXTENSIONS

AVAILABLE ON ALL NOTCH DUMP WAGONS FOR USE WHEN HAULING LIGHT WEIGHT MATERIAL



WATCH A NOTCH DUMP WAGON DEMO ON OUR WEBSITE

WWW.NOTCHMFGINC.COM

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.